

# INVT Electric

## GD350-19



### Гарантія

24 місяці



### З 2010 р.

власний імпорт



### Масштаб

>43000 шт.

встановлено  
нами в Україні



### Переваги

Авторизований  
сервісний центр



### Швидкість

>1500 шт. на складі  
(від 0,2 до 350 кВт)



Table 1-1 Power loss and IE class

Model	Relative loss (%)								Standby loss (W)	IE class
	(0;25)	(0;50)	(0;100)	(50;25)	(50;50)	(50;100)	(90;50)	(90;100)		
GD350-19-1R5G-4-B	1.54	1.50	1.67	1.12	1.04	1.45	0.91	1.45	3	IE2
GD350-19-2R2G-4-B	1.21	1.96	2.43	0.80	1.00	1.50	0.83	1.43	5	IE2
GD350-19-004G-4-B	1.13	1.40	2.05	1.14	1.43	2.14	1.41	2.28	6	IE2
GD350-19-5R5G-4-B	0.94	1.27	2.07	1.01	1.38	2.33	1.53	2.60	8	IE2
GD350-19-7R5G-4-B	0.76	0.96	1.53	0.85	1.04	2.25	1.17	1.86	7	IE2
GD350-19-011G-4-B	0.61	0.84	1.55	0.61	1.04	1.97	0.99	2.16	9	IE2
GD350-19-015G-4-B	0.42	0.52	1.27	0.55	0.73	1.46	0.78	1.66	9	IE2
GD350-19-018G-4-B	0.54	0.74	1.2	0.77	1.03	1.70	0.96	1.65	11	IE2
GD350-19-022G-4-B	0.47	0.67	1.21	0.67	0.90	1.54	0.87	1.38	11	IE2
GD350-19-030G-4-B	0.53	0.72	0.71	0.71	0.9	0.85	1.45	1.5	13	IE2
GD350-19-037G-4-B	0.47	0.69	1.39	0.63	0.88	1.60	0.99	1.72	14	IE2
GD350-19-045G-4-B	0.49	0.69	1.39	0.78	1.00	1.64	0.97	1.66	21	IE2
GD350-19-055G-4-B	0.51	0.69	1.26	0.71	0.89	1.47	0.88	1.40	22	IE2
GD350-19-075G-4-B	0.44	0.61	1.12	0.51	0.69	1.29	0.76	1.42	22	IE2
GD350-19-090G-4-B	0.42	0.59	1.15	0.47	0.65	1.29	0.90	1.48	25	IE2
GD350-19-110G-4-B	0.43	0.63	1.30	0.48	0.75	1.64	0.80	1.78	28	IE2
GD350-19-132G-4	0.47	0.59	1.06	0.61	0.71	1.28	0.85	1.43	55	IE2
GD350-19-160G-4	0.59	0.71	1.36	1.22	0.97	1.87	1.00	1.84	55	IE2
GD350-19-185G-4	0.62	0.76	1.21	1.17	1.12	1.70	1.08	1.61	55	IE2
GD350-19-200G-4	0.53	0.71	1.42	0.74	0.94	1.81	1.00	1.84	55	IE2
GD350-19-220G-4	0.33	0.42	0.69	0.85	0.95	1.33	1.10	1.18	80	IE2
GD350-19-250G-4	0.38	0.59	1.22	0.65	0.92	1.67	0.93	1.74	80	IE2
GD350-19-280G-4	0.40	0.59	1.10	0.64	0.89	1.58	1.12	1.35	80	IE2
GD350-19-315G-4	0.56	0.35	0.79	0.94	0.94	1.63	1.36	2.22	80	IE2
GD350-19-355G-4	0.37	0.47	0.98	0.91	1.11	1.95	1.41	2.44	80	IE2
GD350-19-400G-4	0.17	0.26	0.42	0.28	0.41	0.74	0.47	0.92	80	IE2
GD350-19-450G-4	0.31	0.54	0.98	0.46	0.62	1.02	0.67	0.85	80	IE2
GD350-19-500G-4	0.32	0.55	0.98	0.45	0.61	1.02	0.66	0.83	80	IE2

Table 1-2 Rated specifications

Model	Apparent power (kVA)	Rated output power (kW)	Rated output current (A)	Max. working temperature (°C)	Rated power frequency (Hz)	Rated power voltage (V)
GD350-19-1R5G-4-B	2.4	1.5	3.7	50°C Derate 1% for every increase of 1°C when the temperature exceeds 40°C.	50Hz/60Hz Allowed range: 47-63Hz	3PH 380V
GD350-19-2R2G-4-B	3.3	2.2	5			
GD350-19-004G-4-B	6.2	4	9.5			
GD350-19-5R5G-4-B	9.2	5.5	14			
GD350-19-7R5G-4-B	12.2	7.5	18.5			
GD350-19-011G-4-B	16.4	11	25			
GD350-19-015G-4-B	21.0	15	32			
GD350-19-018G-4-B	25.0	18.5	38			
GD350-19-022G-4-B	29.6	22	45			
GD350-19-030G-4-B	39.4	30	60			
GD350-19-037G-4-B	49.3	37	75			
GD350-19-045G-4-B	60.5	45	92			
GD350-19-055G-4-B	75.7	55	115			
GD350-19-075G-4-B	98.7	75	150			
GD350-19-090G-4-B	118.5	90	180			
GD350-19-110G-4-B	141.5	110	215			
GD350-19-132G-4	171.1	132	260			
GD350-19-160G-4	200.7	160	305			
GD350-19-185G-4	223.7	185	340			
GD350-19-200G-4	250.1	200	380			
GD350-19-220G-4	279.7	220	425			
GD350-19-250G-4	315.9	250	480			
GD350-19-280G-4	348.8	280	530			
GD350-19-315G-4	394.9	315	600			
GD350-19-355G-4	427.8	355	650			
GD350-19-400G-4	473.8	400	720			
GD350-19-450G-4	539.7	450	820			
GD350-19-500G-4	566.0	500	860			

Аурум-Електро – більше 10 років  
офіційний імпортер та сервісний центр

**Номер телефону**

099-35-90-777  
096-35-90-777

**E-mail**

shop@aurum-electro.com.ua



**Офіційна адреса сайту**

[www.shop.aurum-electro.com.ua](http://www.shop.aurum-electro.com.ua)